



Specifications and technical information given are indicative and may be subject to change without prior notice. ZDLEI200_ED05/2012/UK

Lei 200

LEI 200, a 200 cups automatic vending machine (also available in the semi-automatic version), espresso coffee from beans + instant products, with 12 push buttons that can be set either as direct selections or pre-selections. Great configuration flexibility and wide choice of versions, with water mains supply or autonomous water kit inside the base cabinet. Selections keypad with innovative Soft Touch Technology (STT), which recognises human touch. Backlit push buttons and easily interchangeable labels inside the front door. Models with Backlit lexan or 7" LCD screen. Illuminated cup station with a height of 170 mm to be able to host a jug and foldaway small cup holder standard on the automatic version. Extractable mixing bowls to make maintenance operations easier. Equipped, in the espresso version, with Bianchi Vending's patented espresso brewer. Tea serpentine kit as standard. Pre-heating boiler with electronical temperature management available on the espresso double-boiler version. The coffee group is produced by Bianchi Vending from their own exclusive projects.

Lei 200 Espresso technical features



LEI 200 ESPRESSO VERSIONS	E4S SINGLE BOILER FULLY AUTOMATIC	E5S SINGLE BOILER SEMI AUTOMATIC	E4S DOUBLE BOILER FULLY AUTOMATIC	E5S DOUBLE BOILER SEMI AUTOMATIC
COFFEE BEANS	1	1	1	1
DRY SUGAR	1	-	1	-
INSTANT CANISTERS	4	5	4	5
DIMENSIONS	H 745 mm x W 510 mm x D 600 mm - Weight 51 kg (espresso automatic version)			
BASE CABINET	H 786.5 mm x W 510 mm x D 555 mm without wall bracket Depth including wall bracket = 610 mm			

TECHNOLOGY



CHARACTERISTICS

POWER SUPPLY FEATURES

230 Vac – 50Hz / 120 Vac – 60 Hz

INTERNAL POWER SUPPLY

All electrical components are supplied at 24 V dc, except for the boiler's heating element and the espresso pump, which are at 230 Vac – 50 Hz

POWER CONSUMPTION

1.80 kW espresso single boiler version

2.50 kW espresso double boiler version

WATER SUPPLY

Fitting connection = 3/4"

PRODUCT CAPACITY

Coffee beans	1.70 kg
Instant coffee	0.85 kg
Barley	0.85 kg (1.75 lt)
Powdered milk	0.55 kg (1.75 lt)
Creamer	1.20 kg (1.75 lt)
Chocolate	3.00 kg (1.75 lt) double canister
Lemon tea	2.00 kg (1.75 lt)
Tea	1.00 kg
Soup	1.25 kg
Sugar	1.70 kg
Stirrers	200 pcs
Cups	200 pcs

AUTONOMY

Standard boiler for Espresso: 1500 W – 150 cc. Double boiler available by adding a boiler 700 W – 180 cc for higher performances (long drinks). Drip tray capacity: 2 litres with electronic safety block. Waste bucket capacity: 200 pucks.

USER INTERFACE

12 selection buttons with STT (Soft Touch Technology) that can be set either as direct selections or pre-selections. 32 character alphanumeric display. 12 buttons optional alphanumeric keypad to manage a slave spiral machine.

ACCESSORIES

Visual Smart Programmer Speed to upload firmware and settings and download settings and audit data, without needing a PC. Telemetry kit (GPRS modem with aerial + clock chip). Settings, telemetry and audit key kit. Chip card kit. IRDA interface. Cup sensor kit. Free vend panel. EXE/MDB kit. Electronics predisposed for telemetry, clock chip and all programming systems. 7" graphic LCD screen to replace the backlit lexan. Autonomous pump kit that can be mounted inside the base cabinet. Side module kit with change-giver to be used when combined with slave spiral machine underneath. Simple cabinet or predisposed for payment systems. Raised base kit to bring machine + cabinet to a height of 163 cm.

Bianchi Vending in Italy • Headquarters • info@bianchivending.com

Corso Africa 9, 24040 Zingonia di Verdellino, Bergamo, Italia

tel. +39.035.45.02.111, fax +39.035.883.304

vending
bianchivending.com